
# ESSEN® HM 28 S

AC/DC+

# Mild Steel electrodes For effective surface treatment

IS: 814:1991, AWS: SFA5.1 E6013

A Rutile Heavy Coated All Position Contact Type General Purpose Welding Electrode for Mild Steel Sheet & Other Fabrications.



## **PROPERTIES**

An all position electrode for high recovery and contact type of welding & for low penetration. Easy to weld at low amperages and at low open circuit voltages. Easy to remove slag.

# **MECHANICAL PROPERTIES**

Tensile strength: 49 Kg / mm<sup>2</sup> (~70,000 psi) Elongation: 21%

## **APPLICATIONS**

For sheet metal fabrication of mild steel strusses, structures, tanks, pipelines, mild steel bases for pumps & motors, frames, fabrication of different sections like T,I,H, beams, also for built up or overlaying on worn out parts of m.s. and also joining dissimilar thickness.

#### WELDING PROCEDURE

Clean weld area. Use AC / DC reverse polarity. Maintain a short arc. Thin gauges can be contact welded

RECOMMENDED AMPERAGE	
Size	Current
2.50mm x 350mm	065 - 090 Amps
3.15mmx 350mm	060 - 125 Amps
4.00 mm x 450 mm	095 - 160 Amps
5.00 mm x 450 mm	120 - 200 Amps

PACKING		
2.50 mm x 350mm 20 Kg	42 pcs/kg (Approx)	
3.15 mm x 350 mm 30 kg	33 pcs/kg (Approx.)	
4.00 mm x 450 mm 42 kg	22 pcs/kg (Approx.)	
5.00 mm x 450 mm 4 2 kg	20 pcs/kg (Approx.)	









'Sai maa', Post : Kadam Wak Wasti via Loni Kalbhor, Post P. B. No.1, Tal.: Haveli,
Dist.: Pune 412201, INDIA TEL: +91 -20 -65781493, 26911175 26911029 FAX: +91-20-26911030

Email: asugar@pn3.vsnl.net.in / essenelectrode@vsnl.net.in

Website: essenelectrode.com